

SAFETY DATA SHEET

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set Syringe (Binder)

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: <u>UHU Epoxy Quick Set Syringe (Binder)</u>

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

FABER - CASTELL 15 GIBBON RD. WINSTON HILLS

NSW 2153

Toll Free: 1800 677 885 Free Fax: 1800 678 608

EMAIL: enquiries @faber-castell.com.au

· Further information obtainable from: CRD

Emergency telephone number:

POISONS INFORMATION CENTRE (PIC)

TEL: 13 11 26

2 Hazards identification

· Classification of the substance or mixture



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves.

Wear eye protection / face protection.

IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

(Contd. of page 1)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Adhesive

· Dangerous components:				
	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	70-100%		
84-66-2	diethyl phthalate	<2.5%		

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water spray

Carbon dioxide

Foam

Fire-extinguishing powder

Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

(Contd. on page 3)

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

84-66-2 diethyl phthalate

NES (Australia) Long-term value: 5 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

· Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 4)

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

(Contd. of page 3)

· Protection of hands:

Rubber gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

9 Physical and chemical properties
Information on basic physical and chemical pro-

Information on basic physical and chemical properties					
General Information					
· Appearance: Form:	Fluid				
Colour:	Colourless				
· Odour:	Weak, characteristic				
· Odour threshold:	Not determined.				
· pH-value at 20 °C:	6				
· Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	296 ℃				
· Flash point:	150 °C				
· Flammability (solid, gaseous):	Not applicable.				
· Ignition temperature:					
Decomposition temperature:	Not determined.				
· Self-igniting:	Product is not selfigniting.				
· Danger of explosion:	Product does not present an explosion hazard.				
· Explosion limits:					
Lower:	Not determined.				
Upper:	Not determined.				
· Vapour pressure:	Not determined.				
Density at 20 °C:	1.1595 g/cm³				
· Relative density	Not determined.				
· Vapour density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				

Viscosity:
 Dynamic at 20 °C:
 Kinematic:
 30000 mPas
 Not determined.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 5)

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

Contd. of page 4)

Solvent content:
Organic solvents:
VOC (EC)

Solids content:
Other information

(Contd. of page 4)

0.0 %
0.00 %

89.0 %
No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with amines.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Version number 6 Revision: 25.06.2015 Printing date 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

· Other adverse effects No further relevant information available.

(Contd. of page 5)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Transport information	
· UN-Number · ADG, IMDG, IATA	UN3082
· UN proper shipping name · ADG	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)) 3082 UMWELTGEFÄHRDENDER STOFF, FLÜSSIG, N.A.G. (Reaktionsprodukt: Bisphenol-A-Epichlorhydrinharze mit durchschnittlichem Molekulargewicht ≤ 700)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
· Transport hazard class(es)	
· ADG, IMDG, IATA · Class · Label	9 Miscellaneous dangerous substances and articles. 9
· Packing group · ADG, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardou substances: reaction product: bisphenol- A (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700)

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

	(Contd. of page
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADG):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and
	articles.
Danger code (Kemler):	90
EMS Number:	F-A,S-F
Transport in bulk according to Anne.	x II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
. , , , ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
. ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (reaction produc
	bisphenol-A-(epichlorhydrin); epoxy resin (number
	average molecular weight ≤ 700)), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances					
All ingredients are listed.					
· Standard for the Uniform Scheduling of Medicines and Poisons					
84-66-2 diethyl phthalate	S10				

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet

Printing date 25.06.2015 Version number 6 Revision: 25.06.2015

Trade name: UHU Epoxy Quick Set syringe (Binder)

May cause an allergic skin reaction.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves.

Wear eve protection / face protection.

IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: CRD
- · Contact:

Frau A. Liar,

Herr Dr. C. Hanf

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

* Data compared to the previous version altered.