Page: 1 of 5

This version issued: May, 2018

# **Section 1 - Identification of the Material and Supplier**

LN Marketing P/L Phone: 03 9775 0713 35A Lakewood Blvd Fax: 03 9775 1428

Carrum Downs VIC 3201, Australia

**Chemical nature:** Pressurised hydrocarbon gas blend

Trade Name: Hot Devil Butane

Product Use: Gas lighter fuel
Creation Date: August, 2013

**This version issued:** May, 2018 and is valid for 5 years from this date.

## **Section 2 - Hazards Identification**

## **Statement of Hazardous Nature**

This product is classified as: Xn, Harmful. N, Dangerous to the environment. F+, Highly Flammable. Not classified as hazardous according to the criteria of SWA.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R11, R67, R51/53. Highly flammable. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment.

**Safety Phrases:** S9, S16, S23, S29, S36, S62, S24/25. Keep container in a well ventilated place. Keep away from sources of ignition - No smoking. Do not breathe gas. Do not empty into drains. Wear suitable protective clothing. If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS. Avoid contact with skin and eyes.

**SUSMP Classification:** None allocated.

ADG Classification: Class 2.1: Flammable gases.

**UN Number:** 1057, LIGHTERS or LIGHTER REFILLS containing flammable gas



# **GHS Signal word: DANGER**

## **HAZARD STATEMENT:**

H224: Extremely flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

## **PREVENTION**

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P243: Take precautionary measures against static discharge.

P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing fumes, mists, vapours or spray.

P271: Use only outdoors or in a well ventilated area.

## **RESPONSE**

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P372: Explosion risk in case of fire.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

## **STORAGE**

P403+P235: Store in a well-ventilated place. Keep cool.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

#### **DISPOSAL**

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

#### **SAFETY DATA SHEET**

Issued by: LN Marketing P/L Phone: 03 9775 0713

Page: 2 of 5

This version issued: May, 2018

# **Emergency Overview**

Physical Description & Colour: Colourless gas

Odour: Mild disagreeable odour

Major Health Hazards: vapours may cause drowsiness and dizziness.

## **Potential Health Effects**

## Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: Vapours may cause drowsiness and dizziness.

## **Skin Contact:**

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. Exposure to liquid or prolonged exposure to direct spray of gas may cause frostbite. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

## **Eye Contact:**

**Short Term Exposure:** Direct exposure to liquid or prolonged exposure to gas spray may cause frostbite and possible eye damage. Exposure to gas spray may also cause dryness of eyes, but this is expected to only cause transient problems. This product is believed to be not irritating to eyes.

Long Term Exposure: No data for health effects associated with long term eye exposure.

## Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. This product is unlikely to cause any irritation problems in the short or long term.

Long Term Exposure: No data for health effects associated with long term ingestion.

## **Carcinogen Status:**

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
butane	106-97-8	98.03	1900	not set
propane	74-98-6	0.77	Asphyxiant	not set
pentane	109-66-0	1.20	1770	2210

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

#### **Section 4 - First Aid Measures**

#### **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** Symptoms are likely due to lack of oxygen in bloodstream. If available, and victim is breathing, administer oxygen. If not breathing, apply mouth to mouth resuscitation. In any event, if victim is unconscious or shows any unusual symptoms, seek urgent medical attention.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

#### **SAFETY DATA SHEET**

Issued by: LN Marketing P/L Phone: 03 9775 0713

Page: 3 of 5

This version issued: May, 2018

# **Section 5 - Fire Fighting Measures**

**Fire and Explosion Hazards**: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Suitable extinguishing media are carbon dioxide, dry chemical, and foam. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point: -60°C (Closed cup)

Upper Flammability Limit: 8.50% Lower Flammability Limit: 1.90% Autoignition temperature: 405°C

Flammability Class: Highly flammable

## **Section 6 - Accidental Release Measures**

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services. Evacuate the area, remove sources of ignition and allow ventilation until gases have dissipated.

# Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits<br/>butaneTWA (mg/m³)STEL (mg/m³)<br/>not setpropaneAsphyxiantnot setpentane17702210

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

**Eye Protection:** Eye protection is not normally necessary when this product is being used. However, if in doubt, wear suitable protective glasses or goggles.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: rubber. **Respirator:** Not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

#### **SAFETY DATA SHEET**

Issued by: LN Marketing P/L Phone: 03 9775 0713

Page: 4 of 5

This version issued: May, 2018

# **Section 9 - Physical and Chemical Properties:**

Physical Description & colour: Colourless gas

**Odour:** Mild disagreeable odour

**Boiling Point:** No specific data. Gas at normal temperatures under atmospheric pressure,

liquid inside pressurised container.

Freezing/Melting Point: -137°C

**Volatiles:** 100% at room temperature

Vapour Pressure: 200.64 kPa Vapour Density: 2.05 (where air = 1)

Specific Gravity: 0.599

Water Solubility: Slightly soluble.

pH: No data.Volatility: Highly volatile.Odour Threshold: No data.

**Evaporation Rate:** Evaporates quickly at atmospheric pressure.

**Coeff Oil/water Distribution**: No data **Autoignition temp:** 405°C

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from heat, flames and sparks. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed. Protect this product from light.

**Incompatibilities:** strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** Polymerisation reactions are unlikely; they are not expected to occur.

# Section 11 - Toxicological Information

**Local Effects:** 

**Target Organs:** There is no data to hand indicating any particular target organs.

## **Classification of Hazardous Ingredients**

Ingredient Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

## Section 12 - Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. This product is biodegradable. It will not accumulate in the soil or water or cause long term problems. This product is unlikely to accumulate in body tissues.

## **Section 13 - Disposal Considerations**

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## **Section 14 - Transport Information**

ADG Code: 1057, LIGHTERS or LIGHTER REFILLS containing flammable gas

Hazchem Code: 2WE Special Provisions: 201

Limited quantities: ADG 7 specifies a Limited Quantity value of NONE for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packaging Group: Not set

#### **SAFETY DATA SHEET**

Issued by: LN Marketing P/L Phone: 03 9775 0713

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Page: 5 of 5

This version issued: May, 2018

## Packaging Method: P002

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

# **Section 15 - Regulatory Information**

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

## **Section 16 - Other Information**

This SDS contains only safety-related information. For other data see product literature.

**Acronyms:** 

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition)

AICS
SWA
Australian Inventory of Chemical Substances
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number

**Hazchem Code** Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

**UN Number** United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, May, 2018. http://www.kilford.com.au/ Phone (02) 9251 4532